

F Form
Material Safety Data Sheet



Cover Sheet for Material Safety Data Sheet

Epoxy Resin

201Mod Epoxy Resin.doc

CI	Chg. Index	Date	Owner		Date	Name	Initials	Dept.	Doc. ID: F0201-03.doc	
	1.0	4/26/99	P. Doucette	Created	4/26/99	P. Doucette	PED	Quality		
				Reviewed	4/26/99	P. Doucette	PED	Quality		
				Released	4/27/99	P. Doucette	PED	Quality		
Computer:		File: C:\ISO9000 Quality Management Manual\F0201-03 .doc								

F Form Material Safety Data Sheet



Product: 2004-Y

Magnolia Plastics, Inc.
5547 Peachtree Industrial Boulevard
Chamblee, GA 30341
Emergency Telephone: Day: 770-451-2777 Night: 800-457-4280
Website: <http://www.magnapoxy.com>

Common Name (Trade name and synonyms): Compound 2004 Yellow

Chemical Name: Modified Epoxy Resin

Chemical Family: Epoxy

CAS Number: Mixture

Section 1: Hazardous Ingredients

<u>Component</u>	<u>%</u>	<u>ACGIH TLV</u>
Epoxy Resin with no established TLV	50-60	
Butyl Glycidyl Ether (BGE)	5-10	25 ppm
Calcium Carbonate (dispersed in resin)	35-45	10 mg/m ³
Yellow Pigments (dispersed in resin)	as Cr <1	0.01 mg/m ³ (as dust)
	As Cd <0.5	0.01 mg/m ³ (as dust)

All ingredients are listed in the TSCA Inventory.

Section 2: Physical and Chemical Characteristics

Boiling Point (°F):	>225°F	Specific Gravity(water=1):	1.60
Vapor Pressure (mm/Hg):	Nil	Volatiles (% by volume):	0
Vapor Density (Air=1):	>1	Evaporation Rate (BuAc=1):	<1
Solubility in Water:	Negligible		
Appearance & Odor:	Yellow liquid; ether odor		

Section 3: Fire and Explosion Data

Flash Point (test method): 173°F (Setaflash) BGE)

Flammable Limits in Air (% by volume): Lel – N/A Uel – N/A

Extinguishing Media: Water spray, foam, dry chemical, CO₂

Special Fire Fighting Precaution/Procedures: Avoid breathing smoke. In confined areas, full fire fighting equipment including a NIOSH approved self-contained breathing apparatus. Cool fire exposed containers with water

Unusual Fire and Explosion Hazards: None

F Form Material Safety Data Sheet



Product: 2004-Y

Section 4: Health Hazard Information

Threshold Limit value (TLV): Not established

ANSI Hazard Class: 4

Signs and Symptoms of exposure: Type of exposure	Signs and Symtopms of exposure
Acute Overexposure	Severely irritating to the skin and eyes possible skin sensitization
Chronic Overexposure	Pre-existing skin and eye disorders may be aggravated
Routes of Exposure	
Inhalation	May cause irritation to skin, eyes and throat
Ingestion	Moderately toxic: may be harmful
Skin Absorption	May be absorbed in toxic amounts
Skin Contact	Severely irritating; may cause skin sensitization
Eye contact	Severely irritating
Carcinogenicity	
NTP	No
IARC	No
OSHA	No

Section 5: Emergency and First Aid Procedures

Skin: Remove contaminated clothing. Wash from skin with soap and water. Launder clothing prior to re-use.

Eyes: Flush with water for 15 minutes while holding eyelids open Get medical attention.

Inhalation: Remove victim to fresh air. Administer oxygen, if necessary.

Ingestion: Do not induce vomiting, Give large doses of water. Get medical attention.

F Form Material Safety Data Sheet



Product: 2004-Y

Section 9: SARA Title III Information (continued):

Section 311: Hazardous Categorization

<u>Acute</u>	<u>Chronic</u>	<u>Fire</u>	<u>Pressure</u>	<u>Reactive</u>	<u>Non-Applicable</u>
X	X	X			

Section 313: Toxic Chemicals

<u>Component</u>	<u>CAS #</u>	<u>%</u>
Chromium (Cr)	7440-47-6	<0.5
Cadmium (Cd)	7440-43-9	<0.5

Section 10: Special Precautions

Warning Statements: **For Industrial Use Only!**
May cause skin irritation. Possible skin sensitizer. Avoid contact with eyes.

Precautions to be taken in Handling and Storage:
Store in a cool, dry area in tightly closed containers. Keep away from skin and eyes. Use with adequate ventilation. Use good hygiene practices.

Other Precautions:

RCRA Status: Not considered to be a hazardous waste
CERCLA: Not listed
DOT Class: Combustible Liquid, N. O. S. in containers rated > 119 gallons
Not listed in containers rated < 119 gallons

Section 11: Miscellaneous

	<u>HMIS Rating</u>
Health:	2
Flammability:	2
Reactivity:	1

This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1919,1200. The information contained herein is based on data available to us and is believed to be accurate. However, Magnolia Plastics, Inc. makes no warranty expressed or implied concerning the accuracy of the information contained herein. It is the user's responsibility to determine the safety, toxicity and suitability of the product described herein. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.

Original Date: 11/20/85 **Revision Date:** 2/27/01 **Revision Number:** 2