

F Form
Material Safety Data Sheet



Cover Sheet for Material Safety Data Sheet (MSDS)
Epoxy Resin and Aliphatic Amine Curing Agent
201Epoxy Aliph.doc

Cl	Chg. Index	Date	Owner		Date	Name	Initials	Dept.	Doc. ID:	
	1.0	4/26/99	P. Doucette	Created	4/26/99	P. Doucette	PED	Quality	F0201-03.doc	
				Reviewed	4/27/99	P. Doucette	PED	Quality		
				Released	4/27/99	P. Doucette	PED	Quality		
Computer:		File: C:\ISO9000 Quality Management Manual\QM Forms\F0201-03 .doc								

F Form Material Safety Data Sheet



Product: 3102-DU, A/CA 319

Magnolia Plastics, Inc.
5547 Peachtree Industrial Boulevard
Chamblee, GA 30341
Emergency Telephone: Day: 770-451-2777 Night: 800-457-4280
Internet: <http://www.magnapoxy.com>

Common Name (Trade name and synonyms): **Magnobond 3102-DU Dark Blue, Part A with Curing Agent CA 319.**

Chemical Name: **Epoxy Resin and Aliphatic Amine Curing Agent**

Chemical Family: **Epoxy; Amine**

CAS Number: **Mixture**

Section 1: Hazardous Ingredients

<u>Component</u>	<u>%</u>	<u>ACGIH TLV</u>
3102DUA: Epoxy Resin with no established TLV	40-50	
Titanium Dioxide (dispersed in resin)	<2	10 mg/m ³
Antimony Trioxide, ATO (dispersed in resin) (as Sb)	10-20	0.5 mg/m ³
CA319: Amine with no established TLV	100	
Hazards: Corrosive, irritant		
All ingredients are listed in the TSCA Inventory		

Section 2: Physical and Chemical Characteristics

Boiling Point (°F):	>225°F	Specific Gravity(water=1)	1.51
Vapor Pressure (mm/Hg):	Nil	Volatiles (% by volume):	0
Vapor Density (Air=1):	>1	Evaporation Rate (BuAc =1)	>1
Solubility in Water:	Negligible		
Appearance & Odor:	3102DUA: Blue liquid;characteristic odor CA319: Amber liquid; ammoniacal odor		

Section 3: Fire and Explosion Data

Flash Point (test method): >200°F (PMCC)

Flammable Limits in Air (% by Volume): **Lel:** N/A **Uel:** N/A

Extinguishing Media: Water Spray, foam, CO₂, dry chemical

Special Fire Fighting Precautions/Procedures: Avoid breathing smoke and vapors. In a confined area, use full fire fighting equipment including an approved self-contained breathing apparatus. Cool fire exposed containers with water.

Unusual Fire and Explosion Hazards: None

F Form Material Safety Data Sheet



Product: 3102-DU, A/CA 319

Section 4: Health Hazard Information

Threshold Limit value (TLV): Not established
ANSI Hazard Class: 3102UA: 4 CA 319: 4
Signs and Symptoms of exposure:

Type of Exposure	Comp	
Acute Overexposure	3102DUA	Moderately irritating to skin and eyes. Possible skin sensitizer.
	CA 319	Vapors are irritating to skin and eyes
Chronic Overexposure	3102DUA	Pre-existing skin and eye disorders may be aggravated
	CA 319	Unknown
Routes of Exposure		
Inhalation	3102DUA	Not likely to produce adverse effects due to low volatility
	CA 319	Vapors are irritating to the skin and eyes
Ingestion	3102DUA	Low order of toxicity
	CA 319	Moderate toxicity; may cause burns of mouth and throat
Skin Absorption	3102DD U	Not likely to be absorbed through the skin in toxic amounts
	CA 319	Repeated or prolonged exposure may be harmful
Skin Contact	3102DUA	Moderately irritating; may cause skin sensitization
	CA 319	May cause chemical burns and or develop allergic skin reaction
Eye Contact	3102DUA	Moderately irritating
	CA 319	Moderately irritating; permanent damage possible on prolonged exposure
Carcinogenicity		
NTP	3102DUA	Contains ATO
	CA 319	No
IARC	3102DUA	Contains ATO
	CA 319	No
OSHA	3102DUA	Contains ATO
	CA 319	No

Section 5: Emergency and First Aid Procedures

Skin: Remove contaminated clothing. Wash from skin with soap and water. Launder clothing prior to re-use.

Eyes: Flush with water for 15 minutes while holding the eyelids open. Get medical attention

Inhalation: Remove victim to fresh air. Administer oxygen if necessary.

Ingestion: Do not induce vomiting. Give large doses of water. Get medical attention.

F Form

Material Safety Data Sheet



Product: 3102-DU, A/CA 319

Section 6: Reactivity Data

Stability: Stable: X Unstable:
Conditions to Avoid: Elevated temperatures
Incompatibility (materials to avoid): Strong oxidizing agents, strong acids and bases
Hazardous Decomposition Products: Oxides of carbon and nitrogen
Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: Large mixtures in bulk. Curing process is exothermic

Section 7: Spill and Leak Procedures:

Steps to be Taken if Material is Spilled or Released:

Avoid contact with liquid and vapors. Wipe with a cloth or collect on absorbent material. For large spills, dike and contain. Pump or shovel into salvage containers.

Waste Disposal Method:

Cure, then bury or incinerate. Remove salvage containers to a waste disposal site operating in compliance to federal, state and local regulations.

Section 8: Special Protection Information

Respiratory Protection (Specific Type):

For excessive vapors or to maintain below the TLV limit, NIOSH approved respirator in compliance to 29 CFR 1910.134.

Ventilation: Local Exhaust: Yes
 Mechanical: Yes
 Other: As required

Protective Gloves: Impervious rubber

Eye Protection: Splash proof chemical goggles

Other Protective Equipment: For prolonged exposure, impervious clothing and boots to minimize personal contact. Eye wash station. Safety shower.

Section 9: SARA Title III Information

Section 302/304: Extremely Hazardous Substance

<u>Component</u>	<u>CAS #</u>	<u>%</u>	<u>RO (lbs)</u>	<u>TPO (lbs)</u>
None				

CERCLA Section 102 (a): Hazardous Substance

<u>Component</u>	<u>CAS #</u>	<u>%</u>	<u>RO (lbs)</u>
Antimony Trioxide	1309-64-4	10-20	1000

F Form Material Safety Data Sheet



Product: 3102-DU, A/CA 319

Section 9: SARA Title III Information (continued):

Section 311: Hazardous Categorization

<u>Acute</u>	<u>Chronic</u>	<u>Fire</u>	<u>Pressure</u>	<u>Reactive</u>	<u>Non-Applicable</u>
X	X				

Section 313: Toxic Chemicals

<u>Component</u>	<u>CAS #</u>	<u>%</u>
Antimony Trioxide	1309-64-4	10-20

Section 10: Special Precautions For Industrial Use only!

Warning Statements: **3102DUA:** .May cause skin irritation; avoid contact with eyes.
 CA 319: Corrosive. May cause severe eye burns.

Precautions to be taken in Handling and Storage:

A: Store in a cool, dry area in tightly closed containers. Avoid contact with skin and eyes. Use with adequate ventilation. Use good hygiene practices.

Other Precautions:

RCRA Status:	Not considered to be a hazardous waste
CERCLA:	Not listed
DOT Class:	3102UA: Not regulated
	CA 319: Corrosive Liquid, Basic, Organic, N.O.S., UN 3267

Section 11: Miscellaneous

	<u>HMIS Rating</u>	
	<u>310DUA</u>	<u>CA 319</u>
Health:	2	3
Flammability:	1	1
Reactivity:	0	0

This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1919,1200. The information contained herein is based on data available to us and is believed to be accurate. However, Magnolia Plastics, Inc. makes no warranty expressed or implied concerning the accuracy of the information contained herein. It is the user's responsibility to determine the safety, toxicity and suitability of the product described herein. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.

Original Date: 1/19/00 **Revision Date:** **Revision Number:**