

**F Form
Material Safety Data Sheet**



**Cover Sheet for Material Safety Data Sheet)
Epoxy Resin and Polyamide Curing Agent
201Epoxy Poly.doc**

Product: 55, A & B

Cl	Chg. Index	Date	Owner		Date	Name	Initials	Dept.	Doc. ID:	
	1.0	4/26/99	P. Doucette	Created	4/26/99	P. Doucette	PED	Quality	F0201-03.doc	
				Reviewed	4/26/99	P. Doucette	PED	Quality		
				Released	4/27/99	P. Doucette	PED	Quality		
Computer:		File: C:\ISO9000 Quality Management Manual\QM Forms\F0201-03 .doc								

F Form Material Safety Data Sheet



Magnolia Plastics, Inc.
5547 Peachtree Industrial Boulevard
Chamblee, GA 30341
Emergency Telephone: Day: 770-451-2777 Night: 800-457-4280
Internet: <http://www.magnapoxy.com>

Common Name (Trade name and synonyms): **Magnobond 55, A & B**

Chemical Name: **Epoxy Resin and Polyamide Amine Curing Agent**

Chemical Family: **Epoxy; Amine**

CAS Number: **Mixture**

Section 1: Hazardous Ingredients

<u>Component</u>	<u>%</u>	<u>ACGIH TLV</u>
A: Epoxy Resin with no established TLV	>85	
Butyl Glycidyl Ether, BGE	10-15	25 ppm (skin)
B: Polyamide with no established TLV	100	

All ingredients are listed in the TSCA Inventory..

Section 2: Physical and Chemical Characteristics

Boiling Point (°F):	>225°F	Specific Gravity(water=1):	1.05
Vapor Pressure (mm/Hg):	Nil	Volatiles (% by volume):	0
Vapor Density (Air=1):	>1	Evaporation Rate (BuAc =1)	>1
Solubility in Water:	Negligible		
Appearance & Odor:	A: Light amber liquid; ether odor B: Tan viscous liquid; ammoniacal odor		

Section 3: Fire and Explosion Data

Flash Point (test method): A: 173°F (PMCC) – BGE; B: >200°F
Flammable Limits in Air Water spray, foam, CO₂, dry chemical

Special Fire Fighting Precautions/Procedures:

Avoid breathing smoke. In confined areas, full fire fighting equipment including a NIOSH approved self-contained breathing apparatus. Cool fire exposed containers with water.

Unusual Fire and Explosion Hazards: None

Product: **55, A & B**

Section 4: Health Hazard Information

F Form Material Safety Data Sheet



Threshold Limit value (TLV): Not established
ANSI Hazard Class: A: 4 B: 4
Signs and Symptoms of exposure:

Type of Exposure	Comp	
Acute Overexposure	A	Severely irritating to skin and eyes. Possible skin sensitizer.
	B	Vapors are extremely irritating to skin and eyes
Chronic Overexposure	A	Pre-existing skin and eye disorders may be aggravated
	B	Unknown
Routes of Exposure		
Inhalation	A	May cause irritation of nose, throat and respiratory tract
	B	Vapors are irritating to the skin, eyes and respiratory tract
Ingestion	A	Moderately toxic; may be harmful
	B	Moderate toxicity; may cause burns of mouth and throat
Skin Absorption	A	May possibly be absorbed through the skin in toxic amounts
	B	Repeated or prolonged exposure may be harmful
Skin Contact	A	Severely irritating; may cause skin sensitization
	B	May cause chemical burns and/ or develop allergic reaction
Eye Contact	A	Severely irritating
	B	Moderately irritating; permanent damage possible on prolonged exposure
Carcinogenicity		
NTP	A	No
	B	No
IARC	A	No
	B	No
OSHA	A	No
	B	No

Section 5: Emergency and First Aid Procedures

Skin: Remove contaminated clothing. Wash from skin with soap and water. Launder clothing prior to re-use.

Eyes: Flush with water for 15 minutes while holding eyelids open

Inhalation: Remove victim to fresh air. Administer oxygen if necessary

Ingestion: Do not induce vomiting. Give large doses of water. Get medical attention.

F Form Material Safety Data Sheet



Product: 55, A & B

Section 6: Reactivity Data

Stability: Stable: X Unstable:
Conditions to Avoid: Elevated temperatures
Incompatibility (materials to avoid): Strong oxidizing agents, strong acids and bases
Hazardous Decomposition Products: Oxides of carbon and nitrogen
Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: Large mixtures in bulk. Curing process is exothermic

Section 7: Spill and Leak Procedures:

Steps to be Taken if Material is Spilled or Released:

Avoid contact with liquid and vapors. Wipe with a cloth or collect on absorbent material. For large spills, dike and contain. Pump or shovel into salvage containers.

Waste Disposal Method:

Cure, then bury or incinerate. Remove salvage containers to a waste disposal site operating in compliance to federal, .

Section 8: Special Protection Information

Respiratory Protection (Specific Type):

For excessive vapors or to maintain below the TLV limit, NIOSH approved respirator in compliance to 29 CFR 1910.134.

Ventilation: Local Exhaust: Yes
Mechanical: Yes
Other: As required
Protective Gloves: Impervious rubber
Eye Protection: Splash-proof chemical goggles
Other Protective Equipment: For prolonged exposure, impervious clothing and shoes to minimize personal contact. Eye wash station; safety shower.

Section 9: SARA Title III Information

Section 302/304: Extremely Hazardous Substance

<u>Component</u>	<u>CAS #</u>	<u>%</u>	<u>RQ (lbs)</u>	<u>TPQ (lbs)</u>
None				

CERCLA Section 102 (a): Hazardous Substance

<u>Component</u>	<u>CAS #</u>	<u>%</u>	<u>RQ (lbs)</u>
None			

Product: 55, A & B

Section 9: SARA Title III Information (continued):

F Form Material Safety Data Sheet



Section 311: Hazardous Categorization

<u>Acute</u> X	<u>Chronic</u> X	<u>Fire</u>	<u>Pressure</u>	<u>Reactive</u>	<u>Non-Applicable</u>
-------------------	---------------------	-------------	-----------------	-----------------	-----------------------

section 313: Toxic Chemicals

<u>Component</u> None	<u>CAS #</u>	<u>%</u>
--------------------------	--------------	----------

Section 10: Special Precautions

Warning Statements:

A:	May cause skin irritation; avoid contact with eyes.
B:	May cause severe eye burns.

Precautions to be taken in Handling and Storage:

Store in a cool, dry area in tightly closed containers. Avoid contact with skin and eyes. Use with adequate ventilation. Use good hygiene practices.

Other Precautions:

RCRA Status:	Not considered to be a hazardous waste
CERCLA:	Not listed
DOT Class:	A: Not regulated in <119 gallon containers Combustible Liquid, N. O. S. . in >119 gallon containers
	B: Not regulated

Section 11: Miscellaneous

	<u>HMIS Rating</u>	
	<u>A</u>	<u>B</u>
Health:	3	2
Flammability:	1	1
Reactivity:	0	0

This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1919,1200. The information contained herein is based on data available to us and is believed to be accurate. However, Magnolia Plastics, Inc. makes no warranty expressed or implied concerning the accuracy of the information contained herein. It is the user's responsibility to determine the safety, toxicity and suitability of the product described herein. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.

Original Date: 5/8/86 **Revision Date:** 1/15/01 **Revision Number:** 4