

F Form  
**Material Safety Data Sheet**



**Cover Sheet for Material Safety Data Sheet**  
**Aliphatic Amine Curing Agent**  
**201 AliphaticCA.doc**

CI	Chg. Index	Date	Owner		Date	Name	Initials	Dept.	Doc. ID:	
	1.0	4/26/99	P. Doucette	Created	4/26/99	P. Doucette	PED	Quality	<b>F0201-03.doc</b>	
				Reviewed	4/27/99	P. Doucette	PED	Quality		
				Released	4/27/99	P. Doucette	PED	Quality		
Computer:		File: C:\ISO9000 Quality Management Manual\F0201-03 .doc								

# F Form Material Safety Data Sheet



Product: 235

Magnolia Plastics, Inc.  
5547 Peachtree Industrial Boulevard  
Chamblee, GA 30341  
Emergency Telephone: Day: 770-451-2777 Night: 800-457-4280  
Internet: <http://www.magnapoxy.com>

---

**Common Name** (Trade name and synonyms): **Curing Agent 235**

**Chemical Name:** Aliphatic Amine Curing Agent

**Chemical Family:** Amine

**CAS Number:** Mixture

---

### **Section 1: Hazardous Ingredients**

<b>Component</b>	<b>%</b>	<b>ACGIH TLV</b>
Diethylene Triamine (DETA)	50-60	1 ppm (skin)
Phenol	2-4	5 ppm (skin)

Hazards: Corrosive, irritant

All ingredients are listed in the TSCA Inventory

### **Section 2: Physical and Chemical Characteristics**

<b>Boiling Point</b> (°F):	>225°F	<b>Specific Gravity</b> (water=1):	0.95
<b>Vapor Pressure</b> (mm/Hg):	Nil	<b>Volatiles</b> (% by volume):	0
<b>Vapor Density</b> (Air=1):	>1	<b>Evaporation Rate</b> (BuAc =1) :	<1
<b>Solubility in Water:</b>	Negligible		
<b>Appearance &amp; Odor:</b>	Amber Liquid, ammoniacal odor		

### **Section 3: Fire and Explosion Data**

**Flash Point** (test method): >200°F (PMCC)

**Flammable Limits in Air** (% by volume): LeL: N/A Uel: N/A

**Extinguishing Media:** Water spray, foam, CO<sub>2</sub>, dry chemical

**Special Fire Fighting Precautions/Procedures:** Avoid breathing smoke. In confined areas, full fire fighting equipment including a self-contained breathing apparatus. Cool fire exposed containers with water.

**Unusual Fire and Explosion Hazards:** None

---

Product: 235

# F Form Material Safety Data Sheet



## Section 4: Health Hazard Information

**Threshold Limit value (TLV):** Not established

**ANSI Hazard Class:** 4

### **Signs and Symptoms of exposure:**

<b>Type of exposure</b>	<b>Signs and Symtopms of exposure</b>
Acute Overexposure	Corrosive. Extremely irritating to eyes and skin
Chronic Overexposure	May aggravate pre-existing eye and skin disorders
<b>Routes of Exposure</b>	
Inhalation	Vapors are irritating and may cause irritation of the respiratory tract
Ingestion	Moderate toxicity. May cause burns of the mouth and throat
Skin Absorption	Repeated or prolonged exposure may be harmful
Skin Contact	May cause chemical burns. May develop allergic skin reaction
Eye contact	Moderately irritating. Permanent Damage posdsible on prolonged exposure
<b>Carcinogenicity</b>	
NTP	No
IARC	No
OSHA	No

## Section 5: Emergency and First Aid Procedures

**Skin:** Remove contaminated Clothing. Wash skin with soap and water. Launder clothing prior to re-use.

**Eyes:** Flush with water for 15 minutes while holding eyelids open. Get medical attention.

**Inhalation:** Remove victim to fresh air. Administer oxygen if necessary.

**Ingestion:** Do not induce vomiting. Give large doses of water. Get medical attention.

# F Form Material Safety Data Sheet



**Product: 235**

---

## Section 6: Reactivity Data

**Stability:** Stable: X  
**Conditions to Avoid:** None  
**Incompatibility (materials to avoid):** Mineral or organic oxides; strong oxidizing agents  
**Hazardous Decomposition Products:** Oxides of carbon and nitrogen  
**Hazardous Polymerization:** May Occur: Will Not Occur: X  
**Conditions to Avoid:** Large mixtures with epoxy resin in bulk. Curing process is exothermic.

## Section 7: Spill and Leak Procedures:

### Steps to be Taken if Material is Spilled or Released:

Avoid contact with liquid or vapors. Wipe with a cloth or collect on absorbent material.  
 Large Spills: Dike and contain. Pump or shovel into salvage vessels.

**Waste Disposal Method:** Cure with epoxy bury, the bury or incinerate. Remove salvage vessels to a waste disposal site operating in compliance with Federal, State and Local regulations.

## Section 8: Special Protection Information

**Respiratory Protection (specific type):** For excessive vapors or to maintain below TLV, a NIOSH approved respirator for organic vapors in compliance with 29 CFR 1910.134.

**Ventilation:** Local Exhaust: Yes  
 Mechanical: Yes  
 Other: As required

**Protective Gloves:** Impervious rubber

**Eye Protection:** Splash proof chemical goggles

**Other Protective Clothing or Equipment:** For prolonged exposure, impervious clothing and boots to minimize personal contact, Eye wash station. Safety shower.

## Section 9: SARA Title III Information

### *Section 302/304: Extremely Hazardous Substance*

<u>Component</u>	<u>CAS #</u>	<u>%</u>	<u>RO (lbs)</u>	<u>TPO (lbs)</u>
Phenol 10,000	108-95-2	2-4	1000	500,

### *CERCLA Section 102 (a): Hazardous Substance*

<u>Component</u>	<u>CAS #</u>	<u>%</u>	<u>RO (lbs)</u>
Phenol	108-95-2	2-4	1000

# F Form Material Safety Data Sheet



**Product: 235**

---

## Section 9: SARA Title III Information (continued):

### Section 311: Hazardous Categorization

<u>Acute</u>	<u>Chronic</u>	<u>Fire</u>	<u>Pressure</u>	<u>Reactive</u>	<u>Non-Applicable</u>
X	X				

### Section 313: Toxic Chemicals

<u>Component</u>	<u>CAS #</u>	<u>%</u>
Phenol	108-95-2	2-4

## Section 10: Special Precautions

**Warning Statements:**      **For Industrial Use Only!**  
Corrosive. May cause severe skin and eye burns.

**Precautions to be taken in Handling and Storage:** Store closed containers. Avoid contact with skin and eyes. Use with adequate ventilation. Use good hygiene practices.

### Other Precautions:

**RCRA Status:** Not considered a hazardous waste.  
**CERCLA:** Not listed  
**DOT Class:** Corrosive Liquid, Basic, Organic, N.O.S., UN 3267

## Section 11: Miscellaneous

	<u>HMIS Rating</u>
<b>Health:</b>	3
<b>Flammability:</b>	1
<b>Reactivity:</b>	0

This Material Safety data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1919,1200. The information contained herein is based on data available to us and is believed to be accurate. However, Magnolia Plastics, Inc. makes no warranty expressed or implied concerning the accuracy of the information contained herein. It is the user's responsibility to determine the safety, toxicity and suitability of the product described herein. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.

**Original Date:** 10/9/85      **Revision Date:** 3/15/01      **Revision Number:** 8